

Dual Action Foaming Drain Maintainer contains citrus oil to break down organic clogs making it easy for the natural bacillus bacteria to digest it. Use in floor drains to sink drains without worry.

- Citrus oil and natural bacteria based
  - Cleans and maintains drains
  - Tube directs foam closer to clog
- Harmless to plumbing and disposals
- No effect on septic or wastewater treatment systems

#### FOR INDUSTRIAL AND INSTITUTIONAL USE

**WARNING:** Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation.



**PREVENTION:** Do not spray on an open flame or other ignition source. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear protective gloves, and eye protection.

**RESPONSE:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.

**STORAGE:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

**DISPOSAL:** Dispose of container in accordance with all Federal, State and Local Regulations regarding waste disposal.

### KEEP THIS AND ALL CLEANING PRODUCTS OUT OF REACH OF CHILDREN

SDS available at [www.neutronindustries.com](http://www.neutronindustries.com) or 1 800-421-8481

Ingredients: Water (7732-18-5), Propane (74-98-6), Butane (106-97-8), C6-C12 Ethoxylated Propoxylated alcohols (68937-66-6), C10-C16 Ethoxylated Propoxylated Alcohols (69227-22-1), Limonene (5989-27-5). Read SDS before using. For more ingredient information visit [www.neutronindustries.com](http://www.neutronindustries.com)

Seller shall not be liable for consequential, special, or indirect damages from use or handling of their product and liability is expressly limited to the refund of purchase price or replacement of product.

**A product of Neutron Industries**  
7107 N Black Canyon Highway  
Phoenix, AZ 85021  
[www.neutronindustries.com](http://www.neutronindustries.com)  
800-421-8481

22N02

MADE IN THE USA

© Copyright 2022 - Neutron Industries




## Foaming Drain Maintainer



Attach the 24" tube to the nozzle. Insert tube into drain moving it as close to the clog as possible.



Spray liberally. Foam will expand to breakdown organic build-up and clean drain.



Allow 10-15 minutes for foam to work.



Flush drain with water.

Re-apply product periodically to maintain and keep the drain free flowing.



To protect against back splash wear eye protection.

**NET WT: 16 OZ (454g)**